



LED system light and workplace lighting



| | |
|-----------------------------------|-----------------------------------------|
| Product-Nr. | 110914-24 |
| EAN: | 4260556623412 |
| Model: | UNILED SL DC |
| Order number: | 110914-24 |
| Model: | UNILED SL DC |
| Type: | LED system light and workplace lighting |
| Illuminant: | SMD LED |
| Power consumption: | ~72 W |
| Lamp luminous flux: | 11394 lm |
| Lamp luminous efficiency: | ~155 lm/W |
| Light distribution: | Direct |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >85 |
| Supply voltage: | 24V DC ± 10% |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP50 |
| Class of protection: | III |
| Glare control: | Microprisms |
| Beam angle (optics): | 100° |
| Operating temperature: | 14 °F - 140 °F |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | micro prisms cover |
| Height [B] x Width [C]: | ~1,38" x ~3,35" |
| Length [A]: | ~60,83" |
| Weight (net): | ~101 oz |
| Gross weight: | ~127 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | Optional via accessories |
| Mounting accessories: | Optional |
| Made in: | Germany |
| Feature: | high light diffusion |