




LED surface-mounted luminaire



<b>Product-Nr.</b>	111010-02
<b>EAN:</b>	4260556624013
<b>Model:</b>	LEANLED II Clear
<b>Order number:</b>	111010-02
<b>Model:</b>	LEANLED II Clear
<b>Type:</b>	LED surface-mounted luminaire
<b>Illuminant:</b>	SMD LED
<b>Power consumption:</b>	~6,5 W
<b>Lamp luminous flux:</b>	1125 lm
<b>Lamp luminous efficiency:</b>	~173 lm/W
<b>Light distribution:</b>	Direct
<b>Light colour:</b>	5700K 3-step MacAdam
<b>Colour rendering (Ra):</b>	>85
<b>Supply voltage:</b>	24V DC ± 10%
<b>Connection (connector):</b>	M12 A-coded
<b>Degree of protection:</b>	IP54
<b>Class of protection:</b>	III
<b>Beam angle (optics):</b>	120°
<b>Operating temperature:</b>	14 °F - 140 °F
<b>Lamps lifetime:</b>	> 100,000 h (L80/B10)
<b>Housing material:</b>	aluminium
<b>Cover material:</b>	Polycarbonat, clear, shatterproof
<b>Height [B] x Width [C]:</b>	~1,22" x ~1,02"
<b>Length [A]:</b>	~10,24"
<b>Weight (net):</b>	~8 oz
<b>Gross weight:</b>	~10 oz
<b>Risk group (DIN EN 62471):</b>	Free group
<b>Markings:</b>	CE, UKCA, ETL Listed (5003529), D mark
<b>Dimmable:</b>	Optional via accessories
<b>Mounting accessories:</b>	2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope
<b>Made in:</b>	Germany