

LED surface-mounted luminaire



Product-Nr.	111010-05
EAN:	4260556624044
Model:	LEANLED II Clear

Order number:	111010-05
Model:	LEANLED II Clear

Type:	LED surface-mounted luminaire
--------------	-------------------------------

Illuminant:	SMD LED
--------------------	---------

Power consumption:	~19,5 W
---------------------------	---------

Lamp luminous flux:	3375 lm
----------------------------	---------

Lamp luminous efficiency:	~173 lm/W
----------------------------------	-----------

Light distribution:	Direct
----------------------------	--------

Light colour:	5700K 3-step MacAdam
----------------------	----------------------

Colour rendering (Ra):	>85
-------------------------------	-----

Supply voltage:	24V DC ± 10%
------------------------	--------------

Connection (connector):	M12 A-coded
--------------------------------	-------------

Degree of protection:	IP54
------------------------------	------

Class of protection:	III
-----------------------------	-----

Beam angle (optics):	120°
-----------------------------	------

Operating temperature:	14 °F - 140 °F
-------------------------------	----------------

Lamps lifetime:	> 100,000 h (L80/B10)
------------------------	-----------------------

Housing material:	aluminium
--------------------------	-----------

Cover material:	Polycarbonat, clear, shatterproof
------------------------	-----------------------------------

Height [B] x Width [C]:	~1,22" x ~1,02"
--------------------------------	-----------------

Length [A]:	~29,92"
--------------------	---------

Weight (net):	~22 oz
----------------------	--------

Gross weight:	~25 oz
----------------------	--------


Risk group (DIN EN 62471):	Free group
-----------------------------------	------------

Markings:	CE, UKCA, ETL Listed (5003529), D mark
------------------	--

Dimmable:	Optional via accessories
------------------	--------------------------

Mounting accessories:	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
------------------------------	---

Made in:	Germany
-----------------	---------



Abstand d=100 cm

E_{max} = 695 lux

E_{min} = 910 lux

E_{av} = 447 lux

