




LED surface-mounted luminaire



Abstand d=100 cm

E_{max} = 199 lux
E_{min} = 259 lux
E_{avg} = 126 lux



| | |
|-----------------------------------|---|
| Product-Nr. | 111010-13 |
| EAN: | 4260556624099 |
| Model: | LEANLED II Opal White |
| Order number: | 111010-13 |
| Model: | LEANLED II Opal White |
| Type: | LED surface-mounted luminaire |
| Illuminant: | SMD LED |
| Power consumption: | ~8,6 W |
| Lamp luminous flux: | 1500 lm |
| Lamp luminous efficiency: | ~173 lm/W |
| Light distribution: | Direct |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >85 |
| Supply voltage: | 24V DC ± 10% |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP54 |
| Class of protection: | III |
| Glare control: | opal white |
| Beam angle (optics): | 120° |
| Operating temperature: | 14 °F - 140 °F |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | polycarbonate, soft |
| Height [B] x Width [C]: | ~1,22" x ~1,02" |
| Length [A]: | ~13,78" |
| Weight (net): | ~11 oz |
| Gross weight: | ~13 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529), D mark |
| Dimmable: | Optional via accessories |
| Mounting accessories: | 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope |
| Made in: | Germany |