LED2WORK
INTELLIGENCE IN LIGHT

LED surface-mounted luminaire

Product-Nr.	111010-22
EAN:	4260556624150
Model:	LEANLED II Clear Cascadeable







Order number:	111010-22
Model:	LEANLED II Clear Cascadeable
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~6,5 W
Lamp luminous flux:	1125 lm
Lamp luminous efficiency:	~173 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC ± 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP54
Class of protection:	III
Beam angle (optics):	120°
Operating temperature:	14 °F - 140 °F
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	polycarbonat, clear, shatterproof
Height [B] x Width [C]:	~1,22“ x ~1,02“
Length [A]:	~10,24“
Weight (net):	~7 oz
Gross weight:	~9 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Dimmable:	Optional via accessories
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope
Made in:	Germany
Feature:	cascadable, several luminiares can be interlinked electrically. The entiere power consuption may not exceed 4A DC.
cascadable:	yes

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com