




LED surface-mounted luminaire



Abstand [m] Kegelhalbwinkel [°] Beleuchtungsstärke [lx]
 - - - C90 (Photobezweck 118.4°)
 - - - C80 (Photobezweck 115.4°)

Abstand d=100 cm

E_{max} = 319 lux
 E_{min} = 429 lux
 E_{avg} = 195 lux



Product-Nr.	111010-23
EAN:	4260556624167
Model:	LEANLED II Clear Cascadeable
Order number:	111010-23
Model:	LEANLED II Clear Cascadeable
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~8,6 W
Lamp luminous flux:	1500 lm
Lamp luminous efficiency:	~173 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC ± 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP54
Class of protection:	III
Beam angle (optics):	120°
Operating temperature:	14 °F - 140 °F
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonat, clear, shatterproof
Height [B] x Width [C]:	~1,22" x ~1,02"
Length [A]:	~13,78"
Weight (net):	~11 oz
Gross weight:	~13 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Dimmable:	Optional via accessories
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar moun-ting) in delivery scope
Made in:	Germany
Feature:	cascable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.
cascable:	yes