




LED surface-mounted luminaire



Product-Nr.	111010-26
EAN:	4260556624198
Model:	LEANLED II Clear Cascadeable
Order number:	111010-26
Model:	LEANLED II Clear Cascadeable
Type:	LED surface-mounted luminaire
Illuminant:	SMD LED
Power consumption:	~26 W
Lamp luminous flux:	4500 lm
Lamp luminous efficiency:	~173 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC ± 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP54
Class of protection:	III
Beam angle (optics):	120°
Operating temperature:	14 °F - 140 °F
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	Polycarbonat, clear, shatterproof
Height [B] x Width [C]:	~1,22" x ~1,02"
Length [A]:	~40,16"
Weight (net):	~28 oz
Gross weight:	~32 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529), D mark
Dimmable:	Optional via accessories
Mounting accessories:	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
Made in:	Germany
Feature:	cascable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.
cascable:	yes