


LED surface-mounted light



| | |
|-----------------------------------|---|
| Product-Nr. | 111090-12 |
| EAN: | 4260556624488 |
| Model: | SIGNALLED II RGB |
| Order number: | 111090-12 |
| Model: | SIGNALLED II RGB |
| Type: | LED surface-mounted light |
| Illuminant: | RGB LED |
| Power consumption RED: | ~1,44 W |
| Lamp luminous flux RED: | 91 lm |
| Power consumption GREEN: | ~0,96 W |
| Lamp luminous flux GREEN: | 168 lm |
| Power consumption BLUE: | ~1,44 W |
| Lamp luminous flux BLUE: | 55 lm |
| Light distribution: | Direct |
| Light colour: | RGB colour space (at least 2563 colours) |
| Supply voltage: | 24V DC - 10% +7% (RGB) |
| Connection (connector): | M12 A-coded |
| Degree of protection: | IP54 |
| Class of protection: | III |
| Glare control: | opal white |
| Beam angle (optics): | 120° |
| Operating temperature: | 14 °F - 122 °F |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | aluminium |
| Cover material: | polycarbonate, soft |
| Height [B] x Width [C]: | ~0,98" x ~1,18" |
| Length [A]: | ~10,24" |
| Weight (net): | ~8 oz |
| Gross weight: | ~10 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529), D mark |
| Dimmable: | No |
| Mounting accessories: | 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope |
| Made in: | Germany |
| Feature: | Signalling via flashing and/or coloured light |