


## LED surface-mounted light



<b>Product-Nr.</b>	111090-43
<b>EAN:</b>	4260556626826
<b>Model:</b>	SIGNALLED II RGB-W
<b>Order number:</b>	111090-43
<b>Model:</b>	SIGNALLED II RGB-W
<b>Type:</b>	LED surface-mounted light
<b>Illuminant:</b>	SMD RGB-W Cluster LED
<b>Power consumption white:</b>	~9,6 W
<b>White lamp luminous flux:</b>	1530 lm
<b>Lamp luminous efficiency:</b>	159,38 lm/W
<b>Power consumption RED:</b>	~2,8 W
<b>Lamp luminous flux RED:</b>	184 lm
<b>Power consumption GREEN:</b>	~2 W
<b>Lamp luminous flux GREEN:</b>	336 lm
<b>Power consumption BLUE:</b>	~2,8 W
<b>Lamp luminous flux BLUE:</b>	112 lm
<b>Light distribution:</b>	Direct
<b>Light colour white:</b>	5600K 3-step MacAdam
<b>Supply voltage:</b>	24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W)
<b>Connection (connector):</b>	M12 A-coded
<b>Degree of protection:</b>	IP54
<b>Class of protection:</b>	III
<b>Glare control:</b>	opal white
<b>Beam angle (optics):</b>	120°
<b>Operating temperature:</b>	14 °F - 122 °F
<b>Lamps lifetime:</b>	> 100,000 h (L80/B10)
<b>Housing material:</b>	aluminium
<b>Cover material:</b>	polycarbonate, soft
<b>Height [B] x Width [C]:</b>	~0,98" x ~1,18"
<b>Length [A]:</b>	~13,78"
<b>Weight (net):</b>	~11 oz
<b>Gross weight:</b>	~13 oz
<b>Risk group (DIN EN 62471):</b>	Free group
<b>Markings:</b>	CE, UKCA, ETL Listed (5003529), D mark
<b>Dimmable:</b>	No
<b>Mounting accessories:</b>	2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
<b>Made in:</b>	Germany