




LED workplace light with gooseneck



Abstand d=50 cm
 E_{min} = 3114 lux
 E_{max} = 8584 lux
 E_{avg} = 516 lux



Product-Nr.	121012-01
EAN:	4260556623719
Model:	CENALED SPOT Flexible Arm
Order number:	121012-01
Model:	CENALED SPOT Flexible Arm
Type:	LED workplace light with gooseneck
Illuminant:	High Power LED
Power consumption:	~8,5 W
Lamp luminous flux:	1120 lm
Lamp luminous efficiency:	134 lm/W
Light distribution:	Direct
Light colour:	5000K 3-step MacAdam
Colour rendering (Ra):	>80
Supply voltage:	24V DC \pm 10%
Power supply:	-
Connection (connector):	Connection cable, oil flex, with open cable ends
Degree of protection:	IP67
Class of protection:	III
Beam angle (optics):	30°
Operating temperature:	14 °F - 122 °F
Lamps lifetime:	> 100.000 h (L90/B10)
Housing material:	aluminium (powder finished)
Cover material:	tempered glass, shatterproof
Flex arm length [A]:	19,69"
base height:	59 mm (2,32")
Mounting:	screw-on base
Weight (net):	~59 oz
Gross weight:	~61 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Yes, via push button at the light head, ON/OFF and dimming
Mounting accessories:	Magnet holder plate optional
Made in:	Germany
Feature:	universal workplace light with high protection degree