



LED workplace light with adjustable arm

| | |
|--------------------|------------------------------|
| Product-Nr. | 121012-02 |
| EAN: | 4260556623726 |
| Model: | CENALED SPOT Articulated Arm |

| | |
|---------------|-----------------------------------------|
| Order number: | 121012-02 |
| Model: | CENALED SPOT Articulated Arm |
| Type: | LED workplace light with adjustable arm |
| Illuminant: | High Power LED |

| | |
|---------------------------|----------------------|
| Power consumption: | ~8,5 W |
| Lamp luminous flux: | 1120 lm |
| Lamp luminous efficiency: | 134 lm/W |
| Light distribution: | Direct |
| Light colour: | 5000K 3-step MacAdam |

| | |
|------------------------|------------------|
| Colour rendering (Ra): | >80 |
| Supply voltage: | 24V DC \pm 10% |
| Power supply: | - |

| | |
|-------------------------|--------------------------------------------------|
| Connection (connector): | Connection cable, oil flex, with open cable ends |
| Degree of protection: | IP67 |

| | |
|----------------------|-----|
| Class of protection: | III |
| Beam angle (optics): | 30° |

| | |
|------------------------|----------------|
| Operating temperature: | 14 °F - 122 °F |
|------------------------|----------------|

| | |
|-----------------|-----------------------|
| Lamps lifetime: | > 100.000 h (L90/B10) |
|-----------------|-----------------------|

| | |
|-------------------|-----------------------------|
| Housing material: | aluminium (powder finished) |
|-------------------|-----------------------------|

| | |
|-----------------|------------------------------|
| Cover material: | tempered glass, shatterproof |
|-----------------|------------------------------|

| | |
|--------------------------|-------------------|
| Length articulated arms: | ~13,78" / ~15,75" |
|--------------------------|-------------------|

| | |
|--------------|---------------|
| base height: | 59 mm (2,32") |
|--------------|---------------|

| | |
|---------------|--------|
| Weight (net): | ~83 oz |
|---------------|--------|

| | |
|---------------|---------|
| Gross weight: | ~106 oz |
|---------------|---------|

| | |
|----------------------------|------------|
| Risk group (DIN EN 62471): | Free group |
|----------------------------|------------|

| | |
|-----------|--------------------------------|
| Markings: | CE, UKCA, ETL Listed (5003529) |
|-----------|--------------------------------|

| | |
|-----------|------------------------------------------------------------|
| Dimmable: | Yes, via push button at the light head, ON/OFF and dimming |
|-----------|------------------------------------------------------------|

| | |
|-----------------------|------------------------------|
| Mounting accessories: | Magnet holder plate optional |
|-----------------------|------------------------------|

| | |
|----------|---------|
| Made in: | Germany |
|----------|---------|

| | |
|----------|-------------------------------------------------------|
| Feature: | universal workplace light with high protection degree |
|----------|-------------------------------------------------------|

Abstand d=50 cm

E_{min}= 3114 luxE_{max}= 8584 luxE_{avg}= 516 lux