pofiled light with t-slot backsided

Product-Nr.	150714-01
EAN:	4260556623795
Model:	PROFILED DC









Order number:	150714-01
Model:	PROFILED DC
Type:	pofiled light with t-slot backsided
Illuminant:	SMD LED
Power consumption:	~23 W
Lamp luminous flux:	3674 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC ± 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP40
Class of protection:	III
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	14 °F - 140 °F
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	~2,56“ x ~1,77“
Length [A]:	~39,37“
Weight (net):	~75 oz
Gross weight:	~100 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional via accessories
Mounting accessories:	Optional
Made in:	Germany
Feature:	universal lighting and/or system light

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com