


profiled light with t-slot backsided



Product-Nr.	150914-02
EAN:	4260556625379
Model:	PROFILED DC
Order number:	150914-02
Model:	PROFILED DC
Type:	profiled light with t-slot backsided
Illuminant:	SMD LED
Power consumption:	~37 W
Lamp luminous flux:	5678 lm
Lamp luminous efficiency:	~155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC ± 10%
Connection (connector):	M12 A-coded
Degree of protection:	IP40
Class of protection:	III
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	14 °F - 140 °F
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	~2,56" x ~1,77"
Length [A]:	~59,06"
Weight (net):	~135 oz
Gross weight:	~164 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Internal dimmer control
Mounting accessories:	Optional
Made in:	Germany
Feature:	with dimming control, universally accepted as workbench