LED recessed luminaire for machines

Product-Nr.	153010-11
EAN:	4260556625430
Model:	FIELDLED EVO Integrated, M12 front-end







Order number:	153010-11
Model:	FIELDLED EVO Integrated, M12 front-end
Type:	LED recessed luminaire for machines
Illuminant:	SMD LED
Power consumption:	~19 W
Lamp luminous flux:	3000 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC ± 10%
Connection (connector):	M12 A-coded, end face
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	Microprisms
Beam angle (optics):	100°
Operating temperature:	-22 °F - 140 °F
Storage temperature:	-22 °F - 176 °F (-30 °C - +80 °C)
Lamps lifetime:	> 100,000 h (L80/B10)
Vibration resistance:	At 10 to 55 Hz (amplitude ~0.01“)
Shock resistance:	Up to ~2 oz
Housing material:	aluminium
Cover material:	ESG (toughened tempered glass), shatterproof
Height [B] x Width [C]:	~1,18“ x ~3,78“
Length [A]:	~11,02“
Weight (net):	~42 oz
Gross weight:	~47 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional via accessories
Made in:	Germany

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com