LED surface-mounted light for machines and systems

Product-Nr.	154410-02
EAN:	4260556625935
Model:	TUBELED_25 Cascadeable







Order number:	154410-02
Model:	TUBELED_25 Cascadeable
Type:	LED surface-mounted light for machines and systems
Illuminant:	SMD LED
Power consumption:	~17,2 W
Lamp luminous flux:	2666 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	Light Forming Technolology
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC ± 10%
Connection (connector):	M8 A-coded
Degree of protection:	IP67
Class of protection:	III
Glare control:	diffused safety glass
Beam angle (optics):	100°
Operating temperature:	-22 °F - 131 °F
Storage temperature:	-22 °F - 176 °F (-30 °C - +80 °C)
Lamps lifetime:	> 100,000 h (L80/B10)
Vibration resistance:	At 10 to 55 Hz (amplitude ~0.01“)
Shock resistance:	Up to ~2 oz
Housing material:	aluminium
Cover material:	tempered glass, 4 mm (0,16“)
Height [B] x Width [C]:	~0,91“ x ~1,1“
Length [A]:	~27,76“
Weight (net):	~5 oz
Gross weight:	~26 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional via accessories
Mounting accessories:	Optional
Made in:	Germany
Feature:	very slim and bright, M8 sensor connector, cascadable

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com