





LED surface-mounted light



Abstand d=100 cm

E_{max} = 541 luxE_{min} = 739 luxE_{av} = 303 lux

| | |
|-------------------------------------|---|
| Product-Nr. | 154590-01 |
| EAN: | 4260556626178 |
| Model: | TUBELED_25 RGB-W |
| Order number: | 154590-01 |
| Model: | TUBELED_25 RGB-W |
| Type: | LED surface-mounted light |
| Illuminant: | SMD RGB-W Cluster LED |
| Power consumption white: | ~24 W |
| White lamp luminous flux: | 3840 lm |
| Lamp luminous efficiency: | ~159 lm/W |
| Power consumption RED: | ~7,2 W |
| Lamp luminous flux RED: | 460 lm |
| Power consumption GREEN: | ~4,8 W |
| Lamp luminous flux GREEN: | 840 lm |
| Power consumption BLUE: | ~7,2 W |
| Lamp luminous flux BLUE: | 280 lm |
| Light distribution: | Direct |
| Light colour white: | 5000K 3-step MacAdam |
| Colour rendering WHITE (Ra): | >85 |
| Supply voltage: | 24 V DC -10 % +7 % (RGB) – 24 V DC ±10 % (W) |
| Connection (connector): | M8 B-coded |
| Degree of protection: | IP67 |
| Class of protection: | III |
| Glare control: | diffused safety glass |
| Beam angle (optics): | 100° |
| Operating temperature: | -22 °F - 131 °F |
| Storage temperature: | -22 °F - 176 °F (-30 °C - +80 °C) |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Vibration resistance: | At 10 to 55 Hz (amplitude ~0.01") |
| Shock resistance: | Up to ~2 oz |
| Housing material: | aluminium |
| Cover material: | tempered glass, shatterproof |
| Height [B] x Width [C]: | ~0,91" x ~1,1" |
| Length [A]: | ~34,25" |
| Weight (net): | ~28 oz |
| Gross weight: | ~31 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | option external, PWM |
| Mounting accessories: | Optional |
| Made in: | Germany |
| Feature: | RGB-W: Illumination and beacon in one light; connection |