## LED system light

| | |
|---|---|
| **Product-Nr.** | 155110-01US |
| **EAN:** | 4260556628431 |
| **Model:** | SYSTEMLED EVO - POWER Daylight White |








| | |
|---|---|
| Order number: | 155110-01US |
| Model: | SYSTEMLED EVO - POWER Daylight White |
| Type: | LED system light |
| Illuminant: | SMD LED |
| Total output incl. driver: | ~41 W |
| Power consumption: | ~36,5 W |
| Lamp luminous flux: | 6500 lm |
| Lamp luminous efficiency: | 184 lm/W |
| Light distribution: | Direct |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >90 (typ. 95) |
| UGR: | <22 |
| Scope of delivery: | 1x Wieland GST18 cable to NEMA5 |
| Supply voltage: | 120-277V AC ± 10%, 50-60 Hz |
| Power supply: | Integrated |
| Connection (connector): | Wieland GST18 |
| Degree of protection: | IP40 |
| Class of protection: | I |
| Glare control: | Microprisms |
| Beam angle (optics): | 90° |
| Operating temperature: | 14 °F - 122 °F |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | aluminum and PMMA |
| Cover material: | NULL |
| Height [B] x Width [C]: | ~1,89“ x ~5,47“ |
| Length [A]: | ~35,35“ |
| Weight (net): | ~90 oz |
| Gross weight: | ~120 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | Optional via accessories |
| Mounting accessories: | Optional |
| Made in: | Germany |
| Feature: | externally dimmable/switchable |




5700K



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com