| | |
|---|---|
| **Product-Nr.** | 156010-11 |
| **EAN:** | 4260556627380 |
| **Model:** | TUBELED_70 EVO AC |







| | |
|---|---|
| Order number: | 156010-11 |
| Model: | TUBELED_70 EVO AC |
| Illuminant: | SMD LED |
| Total output incl. driver: | 14 W |
| Power consumption: | 12 W |
| Lamp luminous flux: | 1899 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >85 |
| Supply voltage: | 120-277V AC ± 10%, 50-60 Hz |
| Power supply: | Integrated |
| Connection (connector): | M12 S-coded |
| Number of poles: | 3 |
| Degree of protection: | IP67/IP69K |
| Class of protection: | I |
| Glare control: | diffuser film |
| Beam angle (optics): | 100° |
| Operating temperature: | -4 °F - 140 °F |
| Storage temperature: | -22 °F - 176 °F (-30 °C - +80 °C) |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Housing material: | Aluminum, glass |
| Height [B] x Width [C]: | ~2,34“ x ~2,76“ |
| Length [A]: | ~11,81“ |
| Weight (net): | ~39 oz |
| Gross weight: | ~49 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | No |
| Mounting accessories: | Optional |
| Made in: | Germany |



LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com