



Product-Nr.	156210-11
EAN:	4260556627403
Model:	TUBELED_70 EVO AC
Order number:	156210-11
Model:	TUBELED_70 EVO AC
Illuminant:	SMD LED
Total output incl. driver:	27 W
Power consumption:	25 W
Lamp luminous flux:	3798 lm
Lamp luminous efficiency:	155 lm/W
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	120-277V AC \pm 10%, 50-60 Hz
Power supply:	Integrated
Connection (connector):	M12 S-coded
Number of poles:	3
Degree of protection:	IP67/IP69K
Class of protection:	I
Glare control:	diffuser film
Beam angle (optics):	100°
Operating temperature:	-4 °F - 140 °F
Storage temperature:	-22 °F - 176 °F (-30 °C - +80 °C)
Lamps lifetime:	> 100,000 h (L80/B10)
Housing material:	Aluminum, glass
Height [B] x Width [C]:	~2,34" x ~2,76"
Length [A]:	~22,05"
Weight (net):	~62 oz
Gross weight:	~75 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	No
Mounting accessories:	Optional
Made in:	Germany