Product-Nr.	156510-01
EAN:	4260556627373
Model:	TUBELED_70 EVO DC





Order number:	156510-01
Model:	TUBELED_70 EVO DC
Illuminant:	SMD LED
Power consumption:	74 W
Lamp luminous flux:	11394 lm
Lamp luminous efficiency:	155 lm/W
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC ± 10%
Power supply:	External
Connection (connector):	M12 A-coded
Number of poles:	3
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare control:	diffuser film
Beam angle (optics):	100°
Operating temperature:	-22 °F - 158 °F
Storage temperature:	-22 °F - 176 °F (-30 °C - +80 °C)
Lamps lifetime:	> 100,000 h (L80/B10)
Vibration resistance:	At 10 to 55 Hz (amplitude ~0.01“)
Shock resistance:	Up to ~2 oz
Housing material:	Aluminum, glass
Height [B] x Width [C]:	~2,34“ x ~2,76“
Length [A]:	~62,2“
Weight (net):	~148 oz
Gross weight:	~199 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional via accessories
Mounting accessories:	Optional
Made in:	Germany

Irrtümer, Systemfehler und Änderungen vorbehalten./
Errors and technical changes excepted. 6.10.2026

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com