



| | |
|-----------------------------------|---|
| Product-Nr. | 157210-01 |
| EAN: | 4260556627465 |
| Model: | VARILED II Power |
| Order number: | 157210-01 |
| Model: | VARILED II Power |
| Illuminant: | SMD LED |
| Power consumption: | 12 W |
| Lamp luminous flux: | 1899 lm |
| Lamp luminous efficiency: | 155 lm/W |
| Light distribution: | Direct |
| Light colour: | 5700K 3-step MacAdam |
| Colour rendering (Ra): | >85 |
| Supply voltage: | 24V DC \pm 10% |
| Power supply: | External |
| Connection (connector): | M8 A-coded |
| Number of poles: | 3 |
| Degree of protection: | IP67 |
| Class of protection: | III |
| Operating temperature: | -22 °F - 140 °F |
| Storage temperature: | -22 °F - 176 °F (-30 °C - +80 °C) |
| Lamps lifetime: | > 100,000 h (L80/B10) |
| Vibration resistance: | At 10 to 55 Hz (amplitude ~0.01") |
| Shock resistance: | Up to ~2 oz |
| Housing material: | aluminium and glass |
| Height [B] x Width [C]: | ~0,54" x ~1,58" |
| Length [A]: | ~11,73" |
| Mounting: | direct |
| Weight (net): | ~11 oz |
| Gross weight: | ~13 oz |
| Risk group (DIN EN 62471): | Free group |
| Markings: | CE, UKCA, ETL Listed (5003529) |
| Dimmable: | Optional through accessories and the M12/M8 adapter 200200-25 |
| Mounting accessories: | No |
| Made in: | Germany |