



Product-Nr.	157310-01
EAN:	4260556627472
Model:	VARILED II Power
Order number:	157310-01
Model:	VARILED II Power
Illuminant:	SMD LED
Power consumption:	16 W
Lamp luminous flux:	2531 lm
Lamp luminous efficiency:	155 lm/W
Light distribution:	Direct
Light colour:	5700K 3-step MacAdam
Colour rendering (Ra):	>85
Supply voltage:	24V DC \pm 10%
Power supply:	External
Connection (connector):	M8 A-coded
Number of poles:	3
Degree of protection:	IP67
Class of protection:	III
Operating temperature:	-22 °F - 140 °F
Storage temperature:	-22 °F - 176 °F (-30 °C - +80 °C)
Lamps lifetime:	> 100,000 h (L80/B10)
Vibration resistance:	At 10 to 55 Hz (amplitude ~0.01")
Shock resistance:	Up to ~2 oz
Housing material:	aluminium and glass
Height [B] x Width [C]:	~0,54" x ~1,58"
Length [A]:	~15,08"
Mounting:	direct
Weight (net):	~12 oz
Gross weight:	~15 oz
Risk group (DIN EN 62471):	Free group
Markings:	CE, UKCA, ETL Listed (5003529)
Dimmable:	Optional through accessories and the M12/M8 adapter 200200-25
Mounting accessories:	No
Made in:	Germany