



1	BN
2	BK
3	GY
PE	GN/YE



Sensor cable, PUR, black

Product-Nr.	200100-15
EAN:	4260556621944
Model:	Sensor Cable, Open/M12 Socket 4-Pin
Order number:	200100-15
Model:	Sensor Cable, Open/M12 Socket 4-Pin
Type:	Sensor cable, PUR, black
Coding:	S-coded
Amount:	1 piece
Suitable for:	LED2WORK 230V AC LED lights with M12 plug, S-coded
Cable length:	~8,2 ft.
Attachment to a luminaire:	Connector socket M12, straight, S-type coded
Cable ends:	open ends, 4 wires / M12 socket, S-type coded, straight
Material:	Contact carrier: plastic, TPU, BK; Coupling: metal, CuZn, nickel-plated; Seal: FPM / FKM; Contacts: metal, CuSn, gold-plated
Nominal voltage:	630V AC 600V AC (UL)
Current load per PIN:	12 A
Ambient temperature:	-22 °F -> 194 °F
Passage resistance (ohms):	< 0,005
Insulation resistance (Ohm):	>= 100 Mio.
Number of poles:	4
RoHS Directive:	Yes
Protection class (mounting):	IP65, IP67, IP68
Cable material:	PUR
Handle body material:	Plastic, TPU, BK
Contact carrier material:	Plastic, TPU, BK
Cover material:	Metal, CuZn, nickel-plated
Sealing material:	FPM / FKM
Contact material:	Metal, CuSn, gold-plated
Standards:	IEC 61076-2-111
Weight (net):	~11 oz
Gross weight:	~12 oz
Markings:	CE