



## Sensor cable, PUR, black

|    |       |
|----|-------|
| 1  | BN    |
| 2  | BK    |
| 3  | GY    |
| PE | GN/YE |



|                                     |  |
|-------------------------------------|--|
| <b>Product-Nr.</b>                  | 200100-16  |
| <b>EAN:</b>                         | 4260556621951  |
| <b>Model:</b>                       | Sensor Cable, Open/M12 Socket 4-Pin  |
| <b>Order number:</b>                | 200100-16  |
| <b>Model:</b>                       | Sensor Cable, Open/M12 Socket 4-Pin  |
| <b>Type:</b>                        | Sensor cable, PUR, black   |
| <b>Coding:</b>                      | S-coded  |
| <b>Amount:</b>                      | 1 piece  |
| <b>Suitable for:</b>                | LED2WORK 230V AC LED lights with M12 plug, S-coded   |
| <b>Cable length:</b>                | ~32,81 ft.   |
| <b>Attachment to a luminaire:</b>   | Connector socket M12, straight, S-type coded   |
| <b>Cable ends:</b>                  | open ends, 4 wires / M12 socket, S-type coded, straight  |
| <b>Material:</b>                    | Contact carrier: plastic, TPU, BK; Coupling: metal, CuZn, nickel-plated; Seal: FPM / FKM; Contacts: metal, CuSn, gold-plated |
| <b>Nominal voltage:</b>             | 630V AC   600V AC (UL)   |
| <b>Current load per PIN:</b>        | 12 A   |
| <b>Ambient temperature:</b>         | -22 °F -> 194 °F   |
| <b>Passage resistance (ohms):</b>   | < 0,005  |
| <b>Insulation resistance (Ohm):</b> | >= 100 Mio.  |
| <b>Number of poles:</b>             | 4  |
| <b>RoHS Directive:</b>              | Yes  |
| <b>Protection class (mounting):</b> | IP65, IP67, IP68   |
| <b>Cable material:</b>              | PUR  |
| <b>Handle body material:</b>        | Plastic, TPU, BK   |
| <b>Contact carrier material:</b>    | Plastic, TPU, BK   |
| <b>Cover material:</b>              | Metal, CuZn, nickel-plated   |
| <b>Sealing material:</b>            | FPM / FKM  |
| <b>Contact material:</b>            | Metal, CuSn, gold-plated   |
| <b>Standards:</b>                   | IEC 61076-2-111  |
| <b>Weight (net):</b>                | ~39 oz   |
| <b>Gross weight:</b>                | ~42 oz   |
| <b>Markings:</b>                    | CE   |