Socket

Product-Nr.	200200-11
EAN:	4260556621975
Model:	Accessory Connection





Insulation resistance (MOhm):	> 100
Order number:	200200-11
Model:	Accessory Connection
Type:	Socket
Coding:	S-coded
Amount:	1 piece
Suitable for:	TUBELED_70 AC, INROLED_50 Ecolab AC
Cable passage:	~0,31“ -> ~0,39“
Material:	Contact carrier: plastic, PA, BK; Coupling: CuZn, nickel-plated; Contacts: metal, CuZn, gold-plated; Cable box: plastic
Nominal voltage:	630V DC
Current load:	12 A
Ambient temperature:	-40 °F -> 176 °F
Passage resistance (ohms):	< 0,003
Insulation resistance (Ohm):	>= 100 Mio.
Protection class (mounting):	IP67
Contact carrier material:	Plastic, PA, BK
Cover material:	CuZn, nickel-plated
Contact material:	Metal, CuZn, gold-plated
Weight (net):	~2 oz
Gross weight:	~4 oz
Markings:	CE
Note:	assemblable

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com