



Distribution box M12-A, 4-way, with fixed cable



Product-Nr.	200300-01
EAN:	4260556622019
Model:	Accessory Connection
Order number:	200300-01
Model:	Accessory Connection
Type:	Distribution box M12-A, 4-way, with fixed cable
Coding:	A-coded
Amount:	1 piece
Suitable for:	LED2WORK lights 24V DC, except for RGB and RGB-W luminaires
Cable length:	~32,81 ft.
Attachment to a luminaire:	Connector socket M12
Material:	Contact carrier: plastic, PA, BK; Seal: FPM/FKM; Contacts: metal, CuSn, gold-plated
Current load per PIN:	2000 mA
Ambient temperature:	-22 °F -> 194 °F
Passage resistance (ohms):	< 0,005
Insulation resistance (Ohm):	>= 100 Mio.
Number of poles:	4
RoHS Directive:	Yes
Protection class (mounting):	IP65, IP67
Cable material:	PUR
Contact carrier material:	Plastic, PA, BK
Sealing material:	FPM/FKM
Contact material:	Metal, CuSn, gold-plated
Standards:	IEC 61076-2-101
Dimensions (mm):	~4,54" x ~2,13" x ~1"
Weight (net):	~18 oz
Gross weight:	~19 oz
Markings:	CE
Note:	Mechanical life: > 100 mating cycles