




Sensor cable, TPE, grey

1	BN
2	WH
3	BU
4	BK



<b>Product-Nr.</b>	201100-04
<b>EAN:</b>	4260556622583
<b>Model:</b>	Sensor Cable, Open/M12 Socket 4-Pin F&B
Order number:	201100-04
<b>Model:</b>	Sensor Cable, Open/M12 Socket 4-Pin F&B
<b>Type:</b>	Sensor cable, TPE, grey
<b>Coding:</b>	A-coded
<b>Amount:</b>	1 piece
<b>Suitable for:</b>	LED2WORK lights 24V DC, except for RGB and RGB-W luminaires
<b>Cable length:</b>	~16,4 ft.
<b>Attachment to a luminaire:</b>	Connector socket M12, straight, EPDM seal, V4A cap nut
<b>Cable ends:</b>	open ends, 4 wires / M12 socket, straight
<b>Material:</b>	Contact carrier: plastic, PP, GY; Coupling: stainless steel, V4A; Seal: EPDM; Contacts: metal, CuSn, gold-plated
<b>Nominal voltage:</b>	250V
<b>Current load per PIN:</b>	4000 mA
<b>Ambient temperature:</b>	-40 °F -> 221 °F
<b>Passage resistance (ohms):</b>	< 0,005
<b>Insulation resistance (Ohm):</b>	>= 100 Mio.
<b>Number of poles:</b>	4
<b>RoHS Directive:</b>	Yes
<b>Protection class (mounting):</b>	IP65, IP67, IP68
<b>Cable material:</b>	TPE
<b>Handle body material:</b>	Plastic, PP, GY
<b>Contact carrier material:</b>	Plastic, PP, GY
<b>Cover material:</b>	Stainless steel, V4A
<b>Sealing material:</b>	EPDM
<b>Contact material:</b>	Metal, CuSn, gold-plated
<b>Standards:</b>	IEC 61076-2-101
<b>Weight (net):</b>	~7 oz
<b>Gross weight:</b>	~9 oz
<b>Markings:</b>	CE
<b>Feature:</b>	Suitable for food and beverages, FDA-approved