Sensor cable for F+B, 16,4 ft., open/M12 socket, A-type encoded

sensor cable, TPE, gray

Product-Nr.	201100-10
EAN:	4260556625980
Model:	Sensor Cable, Open/M12 Socket 5-Pin F&B



Order number:	201100-10
Model:	Sensor Cable, Open/M12 Socket 5-Pin F&B
Type:	sensor cable, TPE, gray
Coding:	A-coded
Amount:	1 piece
Suitable for:	LED2WORK 24V DC luminaires, esp. for RGB and RGB-W lights
Cable length:	~16,4 ft.
Attachment to a luminaire:	connector M12 socket, straight, seal EPDM, cap stainless steel
Cable ends:	open ends, 5 cores / M12 socket, straight
Material:	Contact carrier: plastic, PP, GY; Coupling: stainless steel, V4A; Seal: EPDM; Contacts: metal, CuSn, gold-plated
Ambient temperature:	-40 °F -> 221 °F
Number of poles:	5
Protection class (mounting):	IP65, IP67, IP68, IP69
Handle body material:	plastics, PP, GY
Contact carrier material:	plastics, PP, GY
Cover material:	stainless steel V4A
Contact material:	metal, CuSn, gold-plated
Weight (net):	~7 oz
Gross weight:	~9 oz
Markings:	CE
Feature:	especially suitable for Food+Beverage, FDA approved

Irrtümer, Systemfehler und Änderungen vorbehalten./
Errors and technical changes excepted. 6.10.2026

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com