



DIN rail switching power supply, 24 V DC, for DIN rail mounting

Product-Nr.	210100-01
EAN:	4260556622026
Model:	
Order number:	210100-01
Type:	DIN rail switching power supply, 24 V DC, for DIN rail mounting
Ambient temperature:	-22 °F -> 158 °F
Nominal output voltage:	24V DC
Max. output power:	72 W (76,8 W)
Output current:	3200 mA
Voltage range:	88...264V AC
Input frequency:	47...63 Hz
Max. input current (230 V AC):	850 mA ± 1%
Max. Input current (115 V AC):	1400 mA ± 1%
Output voltage setting range:	24...28V
Overvoltage protection:	29... 33V DC
Efficiency at full load:	89%
Dimensions (mm):	~1,26" x ~4,93" x ~4,02"
Overtemperature protection:	100 °C ± 10 °C
Humidity during operation:	20...95% (non-condensing)
Weight (net):	~16 oz
Gross weight:	~18 oz
Markings:	CE, CB, UKCA, UL508 approved, ITE EN/UL/IEC 60950, BS EN/EN6100-6-2 industrial immunity level
Dimmable:	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
Protective devices:	short circuit protection, overload protection, overvoltage protection, overtemperature protection

