



DIN rail switching power supply, 24 V DC, for DIN rail mounting

|                                       |                                                                                                   |
|---------------------------------------|---------------------------------------------------------------------------------------------------|
| <b>Product-Nr.</b>                    | 210100-04                                                                                         |
| <b>EAN:</b>                           | 4260556622057                                                                                     |
| <b>Model:</b>                         | Constant Voltage Power Supply                                                                     |
| <b>Order number:</b>                  | 210100-04                                                                                         |
| <b>Model:</b>                         | Constant Voltage Power Supply                                                                     |
| <b>Type:</b>                          | DIN rail switching power supply, 24 V DC, for DIN rail mounting                                   |
| <b>Ambient temperature:</b>           | -13 °F -> 158 °F                                                                                  |
| <b>Nominal output voltage:</b>        | 24V DC                                                                                            |
| <b>Max. output power:</b>             | 480 W                                                                                             |
| <b>Output current:</b>                | 20000 mA                                                                                          |
| <b>Voltage range:</b>                 | 90...264V AC                                                                                      |
| <b>Input frequency:</b>               | 47...63 Hz                                                                                        |
| <b>Max. input current (230 V AC):</b> | 2500 mA ± 1%                                                                                      |
| <b>Max. Input current (115 V AC):</b> | 5000 mA ± 1%                                                                                      |
| <b>Output voltage setting range:</b>  | 24...28V                                                                                          |
| <b>Overvoltage protection:</b>        | 29... 33V DC                                                                                      |
| <b>Efficiency at full load:</b>       | 94%                                                                                               |
| <b>Dimensions (mm):</b>               | ~3,37" x ~4,93" x ~5,06"                                                                          |
| <b>Overtemperature protection:</b>    | 90 °C ± 10 °C                                                                                     |
| <b>Humidity during operation:</b>     | 20...95% (non-condensing)                                                                         |
| <b>Weight (net):</b>                  | ~92 oz                                                                                            |
| <b>Gross weight:</b>                  | ~95 oz                                                                                            |
| <b>Markings:</b>                      | CE, CB, UKCA, UL508 approved, ITE EN/UL/IEC 60950                                                 |
| <b>Dimmable:</b>                      | Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH        |
| <b>Protective devices:</b>            | short circuit protection, overload protection, overvoltage protection, overtemperature protection |