# IP67 power source, metal housing, input: open ends, output: M12 socket, cable protection: flexible metal protection hose

| | |
|---|---|
| **Product-Nr.** | 210100-06 |
| **EAN:** | 4260556622071 |
| **Model:** | Constant Voltage Power Supply |




PIN 3 **GND**
PIN 4 **V DC**



| | |
|---|---|
| Order number: | 210100-06 |
| Model: | Constant Voltage Power Supply |
| Type: | IP67 power source, metal housing, input: open ends, output: M12 socket, cable protection: flexible metal protection hose |
| Cable length: | Input: ~0.98 ft. with open ends; output ~0.98 ft. with M12-A |
| Ambient temperature: | -40 °F -> 176 °F |
| Nominal output voltage: | 24V DC |
| Max. output power: | 60 W |
| Output current: | 2500 mA |
| Voltage range: | 90...305V AC |
| Input frequency: | 47...63 Hz |
| Max. input current (230 V AC): | 320 mA ± 1% |
| Max. Input current (115 V AC): | 640 mA ± 1% |
| Output voltage setting range: | 22...27V DC |
| Overvoltage protection: | 28...34V DC |
| Connection to a light: | M12 socket, A-coded |
| Number of poles: | 4 |
| Efficiency at full load: | 89,5 % |
| Degree of protection: | IP67 |
| Dimensions (mm): | ~6,73“ x ~2,42“ x ~1,45“ |
| Overtemperature protection: | 95 °C ± 10 °C |
| Humidity during operation: | 20...95% (non-condensing) |
| Weight (net): | ~39 oz |
| Gross weight: | ~42 oz |
| Markings: | aktive PFC, IP65, IP67, ICC, CB, CE, UKCA, UL8750 Type HL |
| Dimmable: | Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH |
| Protective devices: | short circuit protection, overload protection, overvoltage protection, overtemperature protection |
| Feature: | High degree of protection |

Irrtümer, Systemfehler und Änderungen vorbehalten./
Errors and technical changes excepted. 6.10.2026

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com