



## DIN rail switching power supply, 24 V DC, for DIN rail mounting

<b>Product-Nr.</b>	210100-09
<b>EAN:</b>	4260556622101
<b>Model:</b>	Constant Voltage Power Supply
<b>Order number:</b>	210100-09
<b>Model:</b>	Constant Voltage Power Supply
<b>Type:</b>	DIN rail switching power supply, 24 V DC, for DIN rail mounting
<b>Ambient temperature:</b>	-13 °F -> 158 °F
<b>Nominal output voltage:</b>	24V DC
<b>Max. output power:</b>	120 W
<b>Output current:</b>	5000 mA
<b>Voltage range:</b>	88...264V AC
<b>Input frequency:</b>	47...63 Hz
<b>Max. input current (230 V AC):</b>	700 mA ± 1%
<b>Max. Input current (115 V AC):</b>	1400 mA ± 1%
<b>Output voltage setting range:</b>	24...28V
<b>Overvoltage protection:</b>	29... 33V DC
<b>Efficiency at full load:</b>	91%
<b>Dimensions (mm):</b>	~1,57" x ~4,93" x ~4,47"
<b>Overtemperature protection:</b>	95 °C ± 10 °C
<b>Humidity during operation:</b>	20...95% (non-condensing)
<b>Weight (net):</b>	~21 oz
<b>Gross weight:</b>	~23 oz
<b>Markings:</b>	CE, CB, UKCA, UL508 approved, ITE EN/UL/IEC 60950, BS EN/EN6100-6-2 industrial immunity level
<b>Dimmable:</b>	Power supply unit can be used in conjunction with PWM dimmers available from LED2WORK GmbH
<b>Protective devices:</b>	short circuit protection, overload protection, overvoltage protection, overtemperature protection

