## Surface-mounted device with attachment via an elongated hole

| | |
|---|---|
| **Product-Nr.** | 210700-04 |
| **EAN:** | 4260556623375 |
| **Model:** | LED2WORK DIMMbox |



| | |
|---|---|
| Order number: | 210700-04 |
| Model: | LED2WORK DIMMbox |
| Type: | Surface-mounted device with attachment via an elongated hole |
| Power: | max. 144 W |
| Input/Output Voltage: | 24V DC |
| Current load max.: | 6000 mA |
| Assignment of PIN1 input / output: | 24V DC / - |
| Assignment of PIN2 input / output: | - / - |
| Assignment of PIN3 input / output: | GND / DIM- |
| Assignment of PIN4 input / output: | 24V DC / DIM+ |
| Output voltage: | 24V DC |
| Material: | Casing: ABS |
| Dimming: | Using a rotary potentiometer |
| Input/Output Connection: | M12A male / M12A female connector |
| ON/OFF switch: | Yes |
| Voltage range: | 24V DC |
| Power supply: | External |
| Degree of protection: | IP54 |
| Class of protection: | III |
| Operating temperature: | -4 °F - 122 °F |
| Storage temperature: | -4 °F - 176 °F |
| Dimensions (mm): | ~4,8“ x ~1,5“ x ~1,77“ |
| Weight (net): | ~4 oz |
| Gross weight: | ~5 oz |
| Markings: | CE, UKCA |
| PWM frequency: | ~4,9kHz |
| Feature: | Universal DIMMbox for all LED2WORK 24V DC luminaires, except for RGB |

Irrtümer, Systemfehler und Änderungen vorbehalten./
Errors and technical changes excepted. 6.5.2026

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com