Surface-mounted device with attachment via an elongated hole

Product-Nr.	210700-04
EAN:	4260556623375
Model:	LED2WORK DIMMbox



Order number:	210700-04
Model:	LED2WORK DIMMbox
Type:	Surface-mounted device with attachment via an elongated hole
Power:	max. 144 W
Input/Output Voltage:	24V DC
Current load max.:	6000 mA
Assignment of PIN1 input / output:	24V DC / -
Assignment of PIN2 input / output:	- / -
Assignment of PIN3 input / output:	GND / DIM-
Assignment of PIN4 input / output:	24V DC / DIM+
Output voltage:	24V DC
Material:	Casing: ABS
Dimming:	Using a rotary potentiometer
Input/Output Connection:	M12A male / M12A female connector
ON/OFF switch:	Yes
Voltage range:	24V DC
Power supply:	External
Degree of protection:	IP54
Class of protection:	III
Operating temperature:	-4 °F - 122 °F
Storage temperature:	-4 °F - 176 °F
Dimensions (mm):	~4,8“ x ~1,5“ x ~1,77“
Weight (net):	~4 oz
Gross weight:	~5 oz
Markings:	CE, UKCA
PWM frequency:	~4,9kHz
Feature:	Universal DIMMbox for all LED2WORK 24V DC luminaires, except for RGB

Irrtümer, Systemfehler und Änderungen vorbehalten./
Errors and technical changes excepted. 6.10.2026

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com