## Surface-mounted device with attachment via an elongated hole

| | |
|---|---|
| **Product-Nr.** | 210700-05 |
| **EAN:** | 4260556625409 |
| **Model:** | LED2WORK DIMMbox |



| | |
|---|---|
| Order number: | 210700-05 |
| Model: | LED2WORK DIMMbox |
| Type: | Surface-mounted device with attachment via an elongated hole |
| Power: | 96 W |
| Input/Output Voltage: | 24V DC |
| Current load max.: | 4000 mA |
| Assignment of PIN1 input / output: | 24V DC / - |
| Assignment of PIN2 input / output: | digital input / - |
| Assignment of PIN3 input / output: | GND / GND |
| Assignment of PIN4 input / output: | digital input / +24V out |
| Assignment of PIN5 input / output: | digital input / - |
| Output voltage: | 24V DC |
| Material: | Casing: Plastic |
| Dimming: | Via external control |
| Input/Output Connection: | M12A male / M12A female connector |
| ON/OFF switch: | Yes |
| Degree of protection: | IP54 |
| Operating temperature: | -4 °F - 122 °F |
| Storage temperature: | -4 °F - 176 °F |
| Dimensions (mm): | ~4,8“ x ~1,3“ x ~1,14“ |
| Weight (net): | ~4 oz |
| Gross weight: | ~5 oz |
| Markings: | CE, UKCA |
| PWM frequency: | ~4kHz |
| Feature: | DIMMbox is controlled via an external controller, e.g. PLC |






LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com |
Shop.led2work.com