




Surface-mounted device with attachment via an elongated hole



Product-Nr.	210700-06
EAN:	4260556626949
Model:	LED2WORK DIMMbox
Order number:	210700-06
Model:	LED2WORK DIMMbox
Type:	Surface-mounted device with attachment via an elongated hole
Power:	max. 96 W
Input/Output Voltage:	24V DC
Current load max.:	4000 mA
Assignment of PIN1 input / output:	24V DC / -
Assignment of PIN2 input / output:	- / -
Assignment of PIN3 input / output:	GND / DIM-
Assignment of PIN4 input / output:	24V DC / DIM+
Output voltage:	24V DC
Material:	Casing: ABS
Dimming:	Using a rotary potentiometer
Input/Output Connection:	M12A male / M12A female connector with 9.8 ft cable
ON/OFF switch:	Yes
Voltage range:	24V DC
Power supply:	External
Degree of protection:	IP54
Class of protection:	III
Operating temperature:	-4 °F - 122 °F
Storage temperature:	-4 °F - 176 °F
Dimensions (mm):	~4,8" x ~1,5" x ~1,77"
Weight (net):	~16 oz
Gross weight:	~18 oz
Markings:	CE, UKCA
PWM frequency:	~4,9kHz
Feature:	Universal DIMMbox for all LED2WORK 24V DC luminaires, except for RGB